

ALUMINUM PC CASE Design to be cool!




sound insulated foam

PROVIDES WITH BETTER COOLING FOR EXPANSION CARD/CPU AREA.







PC-60 plus

sound insulated foam PC-V1100 plus PC-V1100B plus PC-V1000 plus PC-V1000B plus

- Device: 5x5.25", 6x3.5" internal(removable), 1 x5.25" to 3.5"converter with a FDD bezel . 1x CD-ROM bezel
- Fan: 12cm bearing fans x2, 12cm blower fan x 1, Air Duct for CPU x 1. Air Duct for PSU fan x 1
- M/B type: ATX M/B (max size: 12"x9.6")
- Front I/O: USB2.0 x2, IEEE1394 x1, MIC x1, EAR x1
- Dim.: PC-V1000/ 210x490x525nim(W,H,D) PC-V1100/ 210x490x550mm(W.H.D)



PC-V2100 plus PC-V2000 plus PC-V2000B plus

• Device: 7x5.25", 12x3.5" internal(removable), 1 x5.25" to 3.5" converter with a FDD bezel, 1x CD-ROM bezel · Fan: 12cm bearing fans x2, 12cm blower fan x1,

Air Duct for CPU x1

• M/B type: EXT ATX M/B (max size: 12"x13") Front I/O: USB2.0 x2, IEEE1394 x1, MIC x1, EAR x1

PC-V2100B plus

 Dim.: PC-V2000/ 210x617x625mm (W.H.D) PC-V2100/ 210x617x650mm (W.H.D)



- Device: 4x5.25", 2x3.5", 5x3.5" internal
- Fan: 12 cm bearing fans x2; 8 cm ball bearing fan x1; 12cm blower fan x1, Air Duct for CPU x1, Air Duct for PSU fan x1
- M/B type: ATX & pentium 4 (max size: 12"x9.6")
- Front I/O: USB2.0 x2 ; IEEE 1394 x1; MIC x1: EAR x1
- Dim.: 210x450x490 mm (W,H,D)
- Slidable M/B tray



• Device: 4x5.25", 3x3.5", 5 x3.5" internal

- · Fan: 8cm bearing fans x 3; 12cm blower fan x1. Air Duct for CPU x1.
- Air Duct for PSU fan x1
- M/B type: ATX M/B (max size: 12"x9.6")
- Front I/O: USB2.0 x2
- Dim.: 210x490x525 mm (W,H,D)
- · Removable M/B tray



PC-7 plus ECONOMIC PC-7B plus ECONOMIC

- Device: 4x5.25", 2x3.5", 3x3.5" internal
- Fan: 12cm bearing fans x1, 8 cm sleeve fan x1
- M/B type: ATX & pentium 4 (max size: 12"x9.6")
- Front I/O: USB2.0 x2; IEEE 1394 x1; MIC x1; EAR x1
- Dim.: 210x450x490 mm (W.H.D)



- Device: 3x5.25", 2x3.5" internal, 1x5.25" to 3.5" converter with a FDD bezel, 1x CD-ROM bezel
- Fan: 6cm ball bearing fan x2, 8cm ball bearing fan x1 M/B type: ATX M/B (max size: 12"x9.6")
- Frontl/O: USB2.0 x 2, IEEE1394 x1, MIC x1, EAR x1

PC-V800 Dim.: 380x160x440 mm (W.H.D) PC-V850 Dim.: 380x160x465 mm (W,H,D)





PC-60

PC-61



PC-6077B

PC-60 / PC-61

- Device: 4x5.25", 3x3.5", 5x3.5" internal
- Fan: 8 cm ball bearing fans x 4
- M/B type: ATX & pentium 4 (max size: 12"x9.6") Front I/O: USB2.0 x 2 ports
- Dim.: 210x450x490 mm (W,H,D)
- · Removable M/B tray
- · Adjustable fan speed

PC-6077 / PC-6077B

- · Device: 7x5.25", 1x HDD rack for 3 hidden HDD, 1 x 5.25" to 3.5" converter with FDD bezel 1x CD-ROM bezel
- Fan: 8 cm bearing fans x 3
- M/B type: EXT ATX M/B (max size: 12"x9.6")
- Front I/O: USB2.0 x 2, IEEE1394 x 1, MIC x 1,
- Dim.: 210x450x490 mm (W.H.D)
- · Removable M/B trav



PC-70 PC-71 PC-7077

PC-7077B

PC-73SL plus





B Group: Interface: IDE Disk Type: 1" height Dim.: 210x146x42mm

C Group:

Interface: IDE

Mobile rack for 3.5" HDD

inner-rack and out-frame can be compatible ey re defined in the same group

A Group: Interface: IDE Disk Type: 1" height Dim.: 210x146x42mm



RH-06F (7200RPM) RH-10F (7200RPM)

- Single sleeve fan in the rear Single sleeve fan in the rear * Mechanical key lock * Mechanical key lock * Inner-rack: iron-coated
 - * ABS 94V0 fireproof plastic

RH-40 (7200RPM)

- Single ball-bearing fan in the rear
- * Electronic key lock Aluminum inner-rack
- * ABS 94V0 fireproof plastic

RH-58 (10000RPM)

- * Dual ball-bearing fan in the front
- Electronic key lock * Aluminum inner-rack

* ABS 94V0 fireproof plastic

W-65A Compatible with middle tower of PC-6X and PC-7 series

RH-007 (7200RPM)

top/bottom cover

* ABS 94V0 fireproof plastic

- Single sleeve fan in the rear
- * Mechanical key lock
- * ABS 94V0 fireproof plastic

RH-32 (7200RPM)

- Single ball-bearing fan in the rear * Electronic key lock
- * Aluminum inner-rack
- * ABS 94V0 fireproof plastic

RH-321 (7200RPM)

- Single ball-bearing fan in the rear
- * Electronic key lock * Aluminum inner-rack

Individual:

Compatible

- * ABS 94V0 fireproof plastic Silver coating color

Interface: IDE

Disk Type: 1" height

Dim.: 214x146x42mm

RH-322 (7200RPM)

- * Single ball-bearing fan in the rear * Electronic key lock
- * Aluminum inner-rack
- * ABS 94V0 fireproof plastic
- * Block color



Compatible with full tower of PC-7X and PC-73SL series

W-65B

W-75B

* CPU air duct for 8cm fan

W-75A



W-V2000A

Transparent side panel

W-V1000A

AD-02 * CPU air duct for 12cm fan

(12 in 1 card reader)

Blower fan

W-V2000B



- * Aluminum blower set
- * 12cm ball Blower fan for expansion card area cooling

or W-SCSI U3-160 Disk Type: 1" height Dim.: 224x146x42mm



- * Dual ball-bearing fan in the front
- * Electronic key lock * Aluminum inner-frame and out-frame, iron-coated top/bottom cover
- * ABS 94V0 fireproof plastic



RH-600 (15000RPM)

- * Dual ball-bearing fan in the front
- * Electronic key lock
- * Aluminum inner-frame and out-frame, and front panel, iron-coated
- ton/bottom cover
- * ABS 94V0 fireproof plastic

RH-68 (15000RPM)

- * Dual ball-bearing fan in the front
- * Electronic key lock
- * Aluminum inner-rack and out-frame.
- * ABS 94V0 fireproof plastic

Wheels stand



WB-01

* Wheels stand for case or other suitcase



Aluminum bezel



* Compacts & slim size multiple-slot for all flash memory cards.

USB 2.0 flash card reader / writer

RH-38

- Single Sunon magentic fan in the rear
- * Electronic key lock
- * ABS 94V0 fireproof plastic

RH-38B

- * Single Sunon magentic fan in the rear
- * Electronic key lock * Aluminum inner-rack
- * ABS 94V0 fireproof plastic



RH-48

- Single Sunon magentic fan in the rear
- * Electronic key lock
- Aluminum inner-rack and out-frome * ABS 94V0 fireproof plastic

RH-48B

- Single Sunon magentic fan in the rear
- Electronic key lock
- * Aluminum inner-rack and out-frome
- * ABS 94V0 fireproof plastic
- Black color

Thermalmeter



- *Fan setup and display
 *Fan speed control and detection *Available for Centigrade and Fahrenheit
- *Icon display for power on /HDD access/fan speed
- *Alarm for fan error
- *3 Temperature sensor

Compatible with full tower of PC-V2000

W-V1000B

Compatible with middle tower of PC-V1000













C-01B

C-01

- * For CD/DVD ROM & 3.5" Floppy
- Only compatible with Lian-Li case
- * Aluminum Bezel design to dress up the look of you Lian-Li aluminum PC case to keep the

front panel neat and tide

serial HDD **Expension HDD Kit**

150MB/sec



Interface: 3.5 SATA Disk Type: 1", height

Dim.: 210x146x42mm

Data transfer rate:

* Fan fail detection

* Support +3.3V



- * Option HDD rack for 3 of 3.5" HDD (2 bays of 5.25" to 3 bays internal) * 1 x 8cm ball bearing fan with filter
- * Compatible with most of case









- * Option HDD rack for 4 of 3.5" HDD (3 bays of 5.25" to 4 bays internal)
- * 1 x 12cm ball bearing fan with filter * Compatible with most of case